



SURGICAL DIATHERMY

Solid State with Bipolar Arrangement

Model: BI-400W & BI-250W

ESSENTIAL FOR TODAY'S SPECIALITY SURGERY

MONOPOLAR WITH BIPOLAR



BI-400W



BI-250W



Perfect for any major or intricate and complicated surgery. Hence, enables optimization of working, depending on the various tissues involved.

Safety of apparatus conforms to international standards.

Facilitates optimum cuts and coagulation. The result; Precision in operation and, also lowest power consumption.

Preferred apparatus for ENT, Neuro Surgery, Gynaecology & General Surgery.

Technical Specifications for Surgical Diathermy / 400 Watts; 250 Watts

Function / Data :	400 Watts	250 Watts
Auto Electro Surgery	400W/80 - 1000	250W/80-1000
Soft Coagulation	150W/80 - 1000	150W/80-200
Input Voltage	220/240V - 50/60 Hz	220/240V - 50/60 Hz
Working Frequency	450 KHz	450 KHz
Output Power Max Cut	350W/ INTO 400 ohms	180 Watts into 400-ohms
Output Power Max - OAG	Two Mode Soft / Normal 200 Watts	120 Watts into 400 ohms

Output Power Activation by Foot and Head Switchers & Security Level - Standard.